



## VEILIGHEIDSSCHOEN S3 SRC MICHIGAN FA307

Een uiterst comfortabele en lichtgewicht veiligheidsschoen voor gekoelde en omgevingsomgevingen.

Ref: FA307

Variants: 4 (37) , 5 (38) , 6 (39) , 6.5 (40) , 7 (41) , 8 (42) , 9 (43) , 10 (44) , 10.5 (45) , 11 (46) , 12 (47) , 13 (48)

Toepassingsgebied: koelmachine +5 to -5°C , koud weer / omgeving

Taakomschrijving: Bestuurder , Picker , Manager



Certification 1: EN ISO 20345:2011  
S3 SRC

Certification Valid Until: 01/11/2025

Updated On: 26/03/2025

# PRODUCT DATA SHEET

The logo for FlexiTog, featuring the brand name in a white, sans-serif font with a registered trademark symbol, set against a red rectangular background.

<b>Weight</b>	1.35 kg
<b>Product Material</b>	Micro-nubuck with anti-abrasion microfibre upper/PU sole
<b>Packaging</b>	Cardboard Box
<b>Storage Instructions</b>	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
<b>Toe Cap</b>	Composite 200J
<b>CAT</b>	II
<b>DoC</b>	The PPE detailed herein meets the criteria of Article 19(b) Risk Category II: internal production control (module B) set out in Annex V, followed by conformity of type based on internal production control (module C) set out in Annex VI, in accordance with PPE Regulation (EU) 2016/425, (UK only) as brought into UK law and amended Essential Health and Safety Requirements.
<b>Commodity Code</b>	64034000 Footwear, incorporating a protective metal toecap, with outer soles of rubber, plastics, leather or composition leather and uppers of leather (excl. sports footwear and orthopaedic footwear)
<b>Country of Origin</b>	Italië

Email: [sales@flexitog.com](mailto:sales@flexitog.com)  
Phone: +31 174 705 840  
Website: <https://www.flexitog.eu>

FlexiTog UK  
FlexiTog UK Ltd  
The Granary Business Park  
School Road, Neatishead  
Norfolk  
NR12 8BU  
Groot-Brittannië

FlexiTog EU  
Schuttevaerweg 17  
3044 BA Rotterdam  
Nederland

## OVERVIEW

---

- Metaalvrij - uitstekend geschikt voor medewerkers die in de buurt van metaaldetectoren werken
- Bovenwerk van micronubuck
- Ademende, slijtvaste voering
- Doorboor weerstand:
- 200J niet-metalen neus
- PU antislip SRC-geclassificeerde zool