



CRISS CROSS GRIP HANDSCHOEN FG14

Stevige en duurzame handschoenen met verbeterde grip, uitstekend geschikt voor picking. Voordelig algemeen gebruik, beide zijden van de handschoen kunnen worden gebruikt.

Ref: FG14

Variants: L

Toepassingsgebied: koelmachine +5 to -5°C , koud weer / omgeving

Taakomschrijving: Picker



Certification 1: EN 388:2016+A1:2018
1,1,3,1,X

Updated On: 12/03/2025

PRODUCT DATA SHEET

The logo for FlexiTog, featuring the brand name in a white, sans-serif font with a registered trademark symbol, set against a red rectangular background.

Weight	0.12 kg
Product Material	Acrylic
Packaging	Cardboard Box
Storage Instructions	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
User Instructions	Keep this item of PPE fastened when in use, for cold protection efficiency. PPE thermal insulation can be affected by an inappropriate cleaning. Do not remove the care label. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of damage to this item, you should immediately replace it.
CAT	II
DoC	The PPE detailed herein meets the criteria of Article 19(b) Risk Category II: internal production control (module B) set out in Annex V, followed by conformity of type based on internal production control (module C) set out in Annex VI, in accordance with PPE Regulation (EU) 2016/425, (UK only) as brought into UK law and amended Essential Health and Safety Requirements.
Commodity Code	61161020 Gloves, impregnated, coated, covered or laminated with rubber, knitted or crocheted
Country of Origin	Pakistan

Email: sales@flexitog.com
Phone: +31 174 705 840
Website: <https://www.flexitog.eu>

FlexiTog UK
FlexiTog UK Ltd
The Granary Business Park
School Road, Neatishead
Norfolk
NR12 8BU
Groot-Brittannië

FlexiTog EU
Schuttevaerweg 17
3044 BA Rotterdam
Nederland

OVERVIEW

- Elastische pols, betere pasvorm en comfort
- PVC Criss Cross - Polsbinding, verhoogde duurzaamheid en slijtage