



## BUTY OCHRONNE S3 SRC ALABAMA FA306

Wyjątkowo komfortowe i lekkie buty ochronne S3 SRC ALABAMA FA306, idealne do pracy w chłodnych i umiarkowanych temperaturach.

Ref: FA306

Variants: 4 (37) , 5 (38) , 6 (39) , 6.5 (40) , 7 (41) , 8 (42) , 9 (43) , 10 (44) , 10.5 (45) , 11 (46) , 12 (47) , 13 (48)

Miejsce przeznaczenia: Zimny magazyn +5 do -5°C , Niskie temperatury na zewnątrz

Stanowisko pracy: Kierowca , Pracownik fizyczny , Menedżer



Certification 1: EN ISO 20345:2011  
S3 SRC

Certification Valid Until: 01/11/2025

Updated On: 12/03/2025

# PRODUCT DATA SHEET

The logo for FlexiTog, featuring the brand name in a white, sans-serif font on a red rectangular background.

<b>Weight</b>	1.29 kg
<b>Product Material</b>	Micro-nubuck with anti-abrasion microfibre upper/PU sole
<b>Packaging</b>	Cardboard Box
<b>Storage Instructions</b>	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
<b>CAT</b>	II
<b>DoC</b>	The PPE detailed herein meets the criteria of Article 19(b) Risk Category II: internal production control (module B) set out in Annex V, followed by conformity of type based on internal production control (module C) set out in Annex VI, in accordance with PPE Regulation (EU) 2016/425, (UK only) as brought into UK law and amended Essential Health and Safety Requirements.
<b>Commodity Code</b>	64034000 Footwear, incorporating a protective metal toecap, with outer soles of rubber, plastics, leather or composition leather and uppers of leather (excl. sports footwear and orthopaedic footwear)
<b>Country of Origin</b>	Włochy

Email: [sales@flexitog.com](mailto:sales@flexitog.com)  
Phone: +31 174 705 840  
Website: <https://www.flexitog.eu>

FlexiTog UK  
FlexiTog UK Ltd  
The Granary Business Park  
School Road, Neatishead  
Norfolk  
NR12 8BU  
Wielka Brytania

FlexiTog EU  
Schuttevaerweg 17  
3044 BA Rotterdam  
Holandia

## OVERVIEW

---

- Metal free - excellent for operatives working near metal detectors.
- micro-nubuck upper.
- Breathable, abrasion resistant lining.
- Pierce resistance.
- 200J non-metallic toecap.
- PU anti-slip SRC rated sole.