



SAFETY BOOT S3 SRC MICHIGAN FA307

An extremely comfortable and lightweight safety boot for chilled and ambient areas.

Ref: FA307

Variants: 4 (37) , 5 (38) , 6 (39) , 6.5 (40) , 7 (41) , 8 (42) , 9 (43) , 10 (44) , 10.5 (45) , 11 (46) , 12 (47) , 13 (48)

Area of use: Chiller +5 to -5°C , Cold Weather / Ambient

Job role: Driver , Picker , Manager



Certification 1: EN ISO 20345:2011 S3 SRC

Certification Valid Until: 01/11/2025

Updated On: 08/04/2025

Email: sales@flexitog.com Phone: +31 174 705 840 Website: https://www.flexitog.eu FlexiTog UK FlexiTog UK Ltd The Granary Business Park School Road, Neatishead Norfolk NR12 8BU United Kingdom FlexiTog EU Schuttevaerweg 17 3044 BA Rotterdam Netherlands





Weight	1.35 kg
Product Material	Micro-nubuck with anti-abrasion microfibre upper/PU sole
Packaging	Cardboard Box
Storage Instructions	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
Тое Сар	Composite 200J
CAT	Π
DoC	The PPE detailed herein meets the criteria of Article 19(b) Risk Category II: internal production control (module B) set out in Annex V, followed by conformity of type based on internal production control (module C) set out in Annex VI, in accordance with PPE Regulation (EU) 2016/425, (UK only) as brought into UK law and amended Essential Health and Safety Requirements.
Commodity Code	64034000 Footwear, incorporating a protective metal toecap, with outer soles of rubber, plastics, leather or composition leather and uppers of leather (excl. sports footwear and orthopaedic footwear)
Country of Origin	Italy

Email: sales@flexitog.com Phone: +31 174 705 840 Website: https://www.flexitog.eu FlexiTog UK FlexiTog UK Ltd The Granary Business Park School Road, Neatishead Norfolk NR12 8BU United Kingdom FlexiTog EU Schuttevaerweg 17 3044 BA Rotterdam Netherlands





OVERVIEW

- Metal free excellent for operatives working near metal detectors.
- micro-nubuck upper.
 Breathable, abrasion resistant lining.
 Pierce resistance.

- 200J non-metallic toecap.
 PU anti-slip SRC rated sole.

Email: sales@flexitog.com Phone: +31 174 705 840 Website: https://www.flexitog.eu FlexiTog UK FlexiTog UK Ltd The Granary Business Park School Road, Neatishead Norfolk NR12 8BU United Kingdom

FlexiTog EU Schuttevaerweg 17 3044 BA Rotterdam Netherlands